

- dodano u verziji 3.2

t=0x0055afaf0 [0, 0]

Contents: [Koha Croatian user group]

- [Koha Croatian user group \(Ä emu sluÅ¾i Keywords to MARC mapping?\)](#)
- [Koha Croatian user group \(Kako se koristi?\)](#)
- [Koha Croatian user group \(Primjer za dodavanje podataka o odgovornosti \(MARC 245c\)\)](#)

Ä emu sluÅ¾i Keywords to MARC mapping?

Ovo je veliko poboljšanje u načinu prikaza podataka u intranetu (testirati OPAC) u sluÅ¾aju kad display nije definiran uz pomoć XSLT.

Omogućuje prikazivanje bilo kojeg polja iz MARC formata, a ne samo onih polja koja su mapirana u Koha bazu.

Kako se koristi?

U admin sučelju intraneta, za svaki framework se odrede ključne riječi i uparene s pojedinim MARC poljima.

Nakon toga se dodaju potrebna polja u ove dvije datoteke:

```
/usr/share/koha/intranet/cgi-bin/catalogue/detail.pl
/usr/share/koha/intranet/htdocs/intranet-tmpl/prog/en/modules/catalogue/detail.
```

Primjer za dodavanje podataka o odgovornosti (MARC 245c)

dodati varijablu responsibility:

```
mglavica@koha-upgrade:/usr/share/koha/intranet/cgi-bin/catalogue$ diff -u detail.pl-before detail
--- detail.pl-before    2009-12-08 22:45:28.740439368 +0100
+++ detail.pl          2009-12-08 21:26:47.280689653 +0100
@@ -90,6 +90,7 @@
 my $marcseriesarray = GetMarcSeries($record,$marcflavour);
 my $marcurlsarray  = GetMarcUrls ($record,$marcflavour);
 my $subtitle       = GetRecordValue('subtitle', $record, $fw);
+my $responsibility = GetRecordValue('responsibility', $record, $fw);

# Get Branches, Itemtypes and Locations
my $branches = GetBranches();
@@ -206,6 +207,7 @@
 MARCSERIES => $marcseriesarray,
 MARCURLS => $marcurlsarray,
 subtitle => $subtitle,
+ responsibility => $responsibility,
 itemdata_ccode => $itemfields{ccode},
 itemdata_enumchron => $itemfields{enumchron},
 itemdata_uri => $itemfields{uri},
```

u template dodati:

```
<!-- TMPL_LOOP NAME="responsibility" -->  
  <!-- TMPL_VAR NAME="subfield" -->  
<!-- /TMPL_LOOP -->
```