

ffz@ffz:~\$

Contents: [Dobrica PavlinuÅjiÄ 's random unstructured stuff]

- Dobrica PavlinuÅjiÄ 's random unstructured stuff (Documents with departments and security settings)
- Dobrica PavlinuÅjiÄ 's random unstructured stuff (Update access to staffonly)
- Dobrica PavlinuÅjiÄ 's random unstructured stuff (Repository)
 - ◆ Dobrica PavlinuÅjiÄ 's random unstructured stuff (backup)
 - ◆ Dobrica PavlinuÅjiÄ 's random unstructured stuff (restore)
 - ◆ Dobrica PavlinuÅjiÄ 's random unstructured stuff (importing from other data source)
- Dobrica PavlinuÅjiÄ 's random unstructured stuff (HASH in export filters with multilang fields)
- Dobrica PavlinuÅjiÄ 's random unstructured stuff (REST API)
- Dobrica PavlinuÅjiÄ 's random unstructured stuff (Fix search with accented characters using backport from git)

Documents with departments and security settings

```
select
  archive.eprintid, department, security
from archive, document
where document.eprintid = archive.eprintid and department like '%informacijske%';
```

Update access to staffonly

```
begin;
update document set security='staffonly' where eprintid in ( select eprintid from archive where d
commit;
```

Repository

backup

```
# prefix all commands with: sudo -u eprints /usr/share/eprints3/bin/
export ffzg archive XMLFiles > /tmp/ffzg.xmlfile
export ffzg subject XML > /tmp/subject.xml
export ffzg user XML > /tmp/user.xml
```

restore

<http://wiki.eprints.org/w/API:bin/import>

```
epadmin erase_data ffzg
```

```
import_subjects --verbose --force --xml ffzg /tmp/subject.xml
import --verbose --migration ffzg user XML /tmp/user.xml
```

```
import --verbose --migration ffzg eprint XML /tmp/ffzg.xmlfile
```

```
generate_static ffzg  
generate_views ffzg
```

importing from other data source

When generating xml file for import documented at http://wiki.eprints.org/w/XML_Export_Format from some other dataset using `--update` is useful to re-run import

```
sudo -u eprints /usr/share/eprints3/bin/import --verbose --migration --enable-file-imports --upda
```

File can be specified in `<url>` tag using <file:///path/on/the/disk/file.pdf> but you need `--unable-file-imports` for this to work!

HASH in export filters with multilang fields

- bug report: <http://www.eprints.org/tech.php/16066.html>
- eprints meta patch: <eprints-plugin-export-simple-multilang.diff>

Even better solution which should work across updates is described at: <http://www.eprints.org/tech.php/16125.html> and our local changes are in <eprints-SimpleMultilang.zip>

REST API

<http://www.eprints.org/tech.php/17435.html>

There is an experimental REST interface that lives at `/rest/`. You will need to give your user the 'rest' role (e.g. in `cfg.d/user_roles.pl`):

```
$c->{user_roles}->{admin} = qw{ rest general ...};
```

(reload Apache to apply the change)

This is driven by `EPrints/Apache/REST.pm`. One mention of it here: http://wiki.eprints.org/w/New_Features_in_EPrints_3.2#REST

Otherwise, I'm working on support CRUD/REST for EPrints URIs:

<http://wiki.eprints.org/w/API:EPrints/Apache/CRUD>

CRUD is missing the ability to update records - what is normally "POST" to an existing URI.

Fix search with accented characters using backport from git

<eprints-fix-search.diff>